

# Material Safety Data Sheet

Material Name: Tin Scrap

ID: NFE-0106

## \*\*\* Section 1 - Chemical Product and Company Identification \*\*\*

Chemical Name: Mixture

Product Use: Scrap metal usage.

### Manufacturer Information

The David J. Joseph Company  
300 Pike Street  
Cincinnati, OH 45202

Contact: Dept. of Safety & Environmental Services  
Phone: (513) 621-8770  
Emergency # (800) 424-9300 - ChemTrec

## \*\*\* Section 2 - Composition / Information on Ingredients \*\*\*

CAS #	Component	Percent
7440-31-5	Tin	>60
7439-92-1	Lead	<40
7440-36-0	Antimony	<16
7440-50-8	Copper	<9
7440-22-4	Silver	<5
7440-43-9	Cadmium	<1
7440-38-2	Arsenic	<1

### Component Information/Information on Non-Hazardous Components

This data sheet is prepared as a guideline for typical uses of scrap materials. The user should be aware that the composition of the scrap can vary based upon the raw materials, processes used, and protective coatings that may have been applied to the original materials. The list of ingredients below are typical ingredients thought to be present in the scrap material. This list includes contaminants that may or may not be present. The percentages given vary from shipment to shipment and may not be entirely accurate for a given shipment and may not be entirely accurate for a given shipment.

Protective coatings, including paints, lubricants, corrosion inhibitors, etc., may have been applied to the material before it came under the control of the recycler. These coatings may contain hazardous materials. Typical hazardous materials contained in these coatings include: lead, zinc, chromium, and cadmium. Some organic materials may also be present. The supplier (recycler) may have no specific knowledge of the particular contaminant. However, it is anticipated that the hazardous materials present in the coatings would generally represent less than 0.1% of the total material present. The health hazards presented by these contaminants would produce their greatest potential for exposure during processes such as melting, cutting, welding. These processes could generate metal fumes that might produce the health hazards identified in section III of this MSDS.

It is suggested that the user protect employees by utilizing engineering controls that reduce exposures to acceptable concentrations. Where engineering controls are not feasible, appropriate personal protective equipment should be utilized.

## \*\*\* Section 3 - Hazards Identification \*\*\*

### Emergency Overview

Product is supplied as scrap metal consisting of tin alloy. This is a non-combustible, non-reactive solid material. Processing of the product for some final uses can include formation of dusts, particulates or fumes which may present certain health hazards. Generation of large quantities of airborne dusts and particulates may produce a fire hazard. Molten metal may react violently with water. Exposure to powder or dusts may be irritating to eyes, nose and throat. Product may cause mechanical abrasions and irritation to the eyes and skin.

# Material Safety Data Sheet

Material Name: Tin Scrap

ID: NFE-0106

## Hazard Statements

CAUTION Dusts, particulates or fumes generated from this product may be irritating to the eyes, skin and respiratory system and may cause fever, chills and muscular aches. May contain copper, antimony and arsenic which may cause allergic skin and/or respiratory sensitization reactions. May contain arsenic, lead and cadmium which may cause cancer. Chronic overexposure to dusts, particulates and fumes may result in gastrointestinal damage, lung, liver and kidney damage, anemia, cardiac abnormalities, neurological damage and may pose a reproductive hazard.

### Potential Health Effects: Eyes

Dust or powder may cause irritation and/or inflammation to the eye tissue. Rubbing may cause abrasion of cornea.

### Potential Health Effects: Skin

Prolonged contact with this product may cause allergic skin sensitization reactions. Dust or powder may irritate the skin. This product may produce skin abrasions, lesions, or cuts.

### Potential Health Effects: Ingestion

Ingestion of this product is unlikely; however if ingested may cause gastrointestinal disturbances, abdominal pain, fever, vomiting, and diarrhea. Ingestion of large amounts of product may produce more serious toxicities including: gastric ulcers, shock, metabolic acidosis, decreased white blood cell count, neurological damage, cardiovascular shock, anemia, liver damage, renal failure, lethargy and coma.

### Potential Health Effects: Inhalation

Product contains components that may cause allergic respiratory sensitization and cancer. Dusts, vapors, and fumes generated during processing may irritate the respiratory system. Overexposure to processing fumes may cause metal fume fever which is an influenza like illness. Symptoms include headache, metallic taste in the mouth, cough, thirst, throat irritation, shortness of breath, fever, sweating and pain in the limbs. Severe acute overexposure or chronic overexposure to dusts or processing fumes may produce more serious toxicities including: lung damage, blood formation effects, nervous and circulatory system damage, kidney damage, and may pose a reproductive hazard.

HMIS Ratings: Health: 1\* Fire: 0 Reactivity: 0 Pers. Prot.: safety glasses with side shields, gloves

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

## \*\*\* Section 4 - First Aid Measures \*\*\*

### First Aid: Eyes

In cases of contact, flush eyes immediately with large amounts of water. If irritation persists get medical attention. In case of mechanical abrasions and cuts, seek medical attention immediately.

### First Aid: Skin

For skin contact, wash immediately with soap and water. Cuts or abrasions should be treated promptly with thorough cleansing of the affected area.

### First Aid: Ingestion

Due to the physical nature of this material, ingestion is unlikely to occur. If ingestion of a large amount does occur, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

### First Aid: Inhalation

If inhaled, immediately remove the affected person to fresh air. If the affected person is not breathing, apply artificial respiration. Seek medical attention immediately.

### First Aid: Notes to Physician

No additional information available.

## \*\*\* Section 5 - Fire Fighting Measures \*\*\*

Flash Point: Not applicable

Upper Flammable Limit (UFL): Not available

Auto Ignition: Not applicable

Rate of Burning: Not applicable

### General Fire Hazards

Dust accumulation from this product may present an explosion hazard in the presence of an ignition source. Coatings and oils applied to the product may enhance flammability.

Method Used: Not applicable

Lower Flammable Limit (LFL): Not available

Flammability Classification: Non-flammable

# Material Safety Data Sheet

Material Name: Tin Scrap

ID: NFE-0106

## Hazardous Combustion Products

This product may release metal oxide fumes by thermal decomposition.

## Extinguishing Media

Dry chemical, soda ash, sand.

## Fire Fighting Equipment/Instructions

Fire fighters should wear full-face, self contained breathing apparatus and impervious protective clothing.

NFPA Ratings: Health: 1 Fire: 0 Reactivity: 0 Other:

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

### \*\*\* Section 6 - Accidental Release Measures \*\*\*

#### Containment Procedures

Containment of this material should not be necessary. If dusts or particulates are generated, eliminate sources of ignition.

#### Clean-Up Procedures

Small pieces of this product may be collected with a broom and shovel. Collect dust or particulates using a vacuum cleaner with a HEPA filter. Put material in suitable, covered, labeled containers.

#### Evacuation Procedures

Isolate area. Keep unnecessary personnel away.

#### Special Procedures

None necessary.

### \*\*\* Section 7 - Handling and Storage \*\*\*

#### Handling Procedures

Do not inhale dusts or vapors produced during thermal processing. Avoid eye and excessive skin contact. Use only with adequate ventilation. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Special care must be taken to avoid buildup of dusts.

#### Storage Procedures

Keep this material in a cool, well-ventilated place.

### \*\*\* Section 8 - Exposure Controls / Personal Protection \*\*\*

#### Exposure Guidelines

##### A: General Product Information

Follow all applicable exposure limits. Keep formation of dusts, particulates and fumes to a minimum.

##### B: Component Exposure Limits

###### Tin (7440-31-5)

ACGIH: metal: 2 mg/m<sup>3</sup> TWA

0.2 mg/m<sup>3</sup> STEL

skin - potential for cutaneous absorption

OSHA: inorganic compounds (except oxides), as Sn: 2 mg/m<sup>3</sup> TWA; organic compounds, as Sn: 0.1 mg/m<sup>3</sup> TWA

organic compounds: Prevent or reduce skin absorption

NIOSH: as Sn: 2 mg/m<sup>3</sup> TWA

###### Lead (7439-92-1)

ACGIH: 0.05 mg/m<sup>3</sup> TWA

OSHA: as Pb: 50 ug/m<sup>3</sup> TWA PEL; 30 ug/m<sup>3</sup> action level; Poison (see 29 CFR 1910.1025)

NIOSH: as Pb: 0.100 mg/m<sup>3</sup> TWA; see Appendix C for supplementary exposure limits

###### Antimony (7440-36-0)

ACGIH: as Sb: 0.5 mg/m<sup>3</sup> TWA

OSHA: as Sb: 0.5 mg/m<sup>3</sup> TWA

NIOSH: 0.5 mg/m<sup>3</sup> TWA

# Material Safety Data Sheet

Material Name: Tin Scrap

ID: NFE-0106

## Copper (7440-50-8)

ACGIH: fume: (0.2) mg/m<sup>3</sup> TWA; dusts and mists, as Cu: (1) mg/m<sup>3</sup> TWA

OSHA: fume, as Cu: 0.1 mg/m<sup>3</sup> TWA

NIOSH: as Cu: 1 mg/m<sup>3</sup> TWA (dusts and mists); 0.1 mg/m<sup>3</sup> TWA (fume)

## Silver (7440-22-4)

ACGIH: metal: 0.1 mg/m<sup>3</sup> TWA

OSHA: as Ag: 0.01 mg/m<sup>3</sup> TWA

NIOSH: as Ag: 0.01 mg/m<sup>3</sup> TWA

## Cadmium (7440-43-9)

ACGIH: elemental, total dust, as Cd: 0.01 mg/m<sup>3</sup> TWA; respirable fraction: 0.002 mg/m<sup>3</sup> TWA

OSHA: 2.5 ug/m<sup>3</sup> TWA action level; 5 ug/m<sup>3</sup> TWA; do not eat, drink or chew tobacco or gum or apply cosmetics in regulated areas; carcinogen; dust can cause lung and kidney disease (see 29 CFR 1910.1027)

NIOSH: NIOSH Potential Occupational Carcinogen - see Appendix A

## Arsenic (7440-38-2)

ACGIH: elemental, as As: 0.01 mg/m<sup>3</sup> TWA

OSHA: organic compounds, as As: 0.5 mg/m<sup>3</sup> TWA

NIOSH: NIOSH Potential Occupational Carcinogen - see Appendix A (organic compounds have no established exposure limit)  
C 0.002 mg/m<sup>3</sup> (15 min)

## Engineering Controls

Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes that may be generated during handling or thermal processing.

## PERSONAL PROTECTIVE EQUIPMENT

### Personal Protective Equipment: Eyes/Face

Wear safety glasses with side shields.

### Personal Protective Equipment: Skin

Use impervious gloves.

### Personal Protective Equipment: Respiratory

When dusts or thermal processing fumes are generated and ventilation is not sufficient to effectively remove them, appropriate NIOSH/MSHA approved respiratory protection must be provided.

### Personal Protective Equipment: General

Use good industrial hygiene practices in handling this material.

## \*\*\* Section 9 - Physical & Chemical Properties \*\*\*

**Appearance:** Depends upon scrap composition, most often appears as a gray metal.

**Odor:** Not available

**Physical State:** Solid

**pH:** Not applicable

**Vapor Pressure:** Not applicable

**Vapor Density:** Not applicable

**Boiling Point:** 4500 deg F (2500 deg C)

**Melting Point:** 450 deg F (230 deg C)

**Solubility (H<sub>2</sub>O):** Insoluble

**Specific Gravity:** 7

## \*\*\* Section 10 - Chemical Stability & Reactivity Information \*\*\*

### Chemical Stability

Stable under normal conditions.

### Chemical Stability: Conditions to Avoid

Avoid dispersion of dust in air. Molten metal may react violently with water. Fine particles, dust or fumes may be flammable or explosive.

# Material Safety Data Sheet

Material Name: Tin Scrap

ID: NFE-0106

## Incompatibility

Tin may react with bromine, bromine trifluoride, chlorine, chlorine trifluoride, copper nitrate, sulfur and potassium peroxide.

## Hazardous Decomposition

Decomposition of this product may yield metallic oxides.

## Hazardous Polymerization

Will not occur.

## \*\*\* Section 11 - Toxicological Information \*\*\*

### Acute and Chronic Toxicity

#### A: General Product Information

No information available for the product. Operations which supply sufficient energy to the product (i.e. welding, high speed grinding or melting) can release dust or fumes which may make components of the product biologically available. Lead has been found to have toxic effects on both the central and peripheral nervous systems. Acute exposure to lead may cause acute encephalopathy which is accompanied by the symptoms of ataxis, coma, and convulsions. As toxicity progresses, symptoms of peripheral neuropathy can develop, as well as some cases of irreversible kidney damage. Exposure to antimony has been known to cause allergic skin sensitization reactions resulting in "antimony spots" on the surface of the skin. Chronic overexposure to antimony may cause gastrointestinal damage, cardiac damage, pneumoconiosis, and obstructive lung disease. With acute exposure, arsenic can cause damage to mucous membranes and skin, and is a severe eye and respiratory tract irritant. Arsenic can also cause severe gastrointestinal damage, muscle cramps, cardiac abnormalities, anemia, decreased white blood cell count, and enlargement of the liver. Arsenic compounds may cause allergic skin sensitization.

Overexposure to copper fume and dust is known to cause metal fume fever, a flu-like illness generally lasting 24 hours or less including symptoms of nausea, chills, sweats, chest tightness, muscle aches and weakness. Chronic exposure to copper fume or dust can cause respiratory tract irritation, hemolytic anemia and allergic contact dermatitis. Other possible effects of copper overexposure include discoloration of skin or hair, and liver and kidney damage. Silver can be harmful if inhaled, absorbed through the skin, or ingested. Symptoms may include gastrointestinal distress, pulmonary edema, convulsions and shock. Chronic overexposure to silver may cause argyria, a gray-blue pigmentation of the skin or organs, loss of strength, convulsive seizures, mild bronchitis, and renal and liver toxicities. Inhalation of cadmium may be harmful with symptoms including tracheobronchitis, pneumonitis, pulmonary edema and death. Overexposure to cadmium may cause liver damage, anemia and irreversible kidney damage.

Dusts and fumes from this product may cause cancer, reproductive and/or birth defects.

#### B: Component Analysis - LD50/LC50

##### Antimony (7440-36-0)

Oral LD50 Rat: 7 gm/kg

##### Cadmium (7440-43-9)

Oral LD50 Mouse: 890 mg/kg

Inhalation LC50 Rat: 25 mg/m<sup>3</sup>/30M

Oral LD50 Rat: 2330 mg/kg

##### Arsenic (7440-38-2)

Oral LD50 Rat: 763 mg/kg

Oral LD50 Mouse: 145 mg/kg

### Carcinogenicity

#### A: General Product Information

No information available for the product. Although some lead salts have produced tumors in animals, the evidence is insufficient to determine the carcinogenicity of lead in humans. There is a possible link between occupational exposure to antimony and lung cancer. Inorganic arsenic can produce lung, skin and lymphatic cancer with long term occupational exposure above the established limits. Cadmium exposure has been linked with increased incidence of lung, prostate and kidney cancer.

#### B: Component Carcinogenicity

# Material Safety Data Sheet

Material Name: Tin Scrap

ID: NFE-0106

## Lead (7439-92-1)

ACGIH: elemental, as Pb; A3 - animal carcinogen

OSHA: as Pb: 50 ug/m3 TWA PEL; 30 ug/m3 action level; Poison (see 29 CFR 1910.1025)

IARC: Monograph 23, Supplement 7; 1987 (and lead compounds; evaluated as a group) (Group 2B (sufficient animal data))

## Cadmium (7440-43-9)

ACGIH: elemental, as Cd: A2-suspected human carcinogen

OSHA: 2.5 ug/m3 TWA action level; 5 ug/m3 TWA; do not eat, drink or chew tobacco or gum or apply cosmetics in regulated areas; carcinogen; dust can cause lung and kidney disease (see 29 CFR 1910.1027)

NIOSH: occupational carcinogen

NTP: suspect carcinogen (Listed under 'Cadmium and certain cadmium compounds') (Possible Select Carcinogen)

IARC: Monograph 58; 1993 (and Cadmium compounds; evaluated as a group) (Group 1 (carcinogenic to humans))

## Arsenic (7440-38-2)

ACGIH: elemental, as As: A1-confirmed human carcinogen

NIOSH: occupational carcinogen

NTP: known carcinogen (Listed under 'Arsenic and certain arsenic compounds') (Select Carcinogen)

IARC: [present] This evaluation applies to the group of chemicals as a whole and not necessarily to all individual chemicals within the group. (Group 1 (carcinogenic to humans))

## Epidemiology

No information available for the product.

## Neurotoxicity

No information available for the product. Symptoms of lead toxicity include behavioral disturbances including irritability, restlessness, insomnia, and other sleep disturbances, fatigue, vertigo, headache, poor memory, tremor, depression, and apathy. In acute lead encephalopathy, neurological damage can be permanent. Neurological changes have been reported after inorganic arsenic inhalation and may include peripheral neuropathy of sensory and motor neurons resulting in numbness, loss of reflex and muscle weakness. Encephalopathy resulting in hallucinations, agitation, emotional changes and memory loss may linger after arsenic exposure.

## Mutagenicity

No information available for the product. Exposure to lead has been reported to cause chromosome aberrations in humans. Elevated frequencies of chromosome aberrations have been shown in workers exposed to cadmium.

## Teratogenicity

No information available for the product. Lead has a wide variety of reproductive effects in humans. It can affect both the male and female reproductive organs as well as egg and sperm production and development. Lead can also cause neurodevelopmental debilitations in children from both prenatal and postnatal exposures. Women working in antimony processing had increased miscarriages, premature births, gynecological disease and developmental delay in their children. There is evidence that arsenic can have reproductive effects in both humans and animals. There may be an increased risk for miscarriage and birth defects in women exposed to arsenic. There is a possible link between copper exposure and miscarriages, and copper can inhibit the motility of human sperm. There is some evidence that cadmium might induce testicular damage in men and may affect male fertility.

## Other Toxicological Information

Under normal conditions of handling, the likelihood of inhaling or ingesting amounts necessary for these effects to occur is very small.

## \*\*\* Section 12 - Ecological Information \*\*\*

## Ecotoxicity

### A: General Product Information

No information available for the product.

### B: Component Analysis - Ecotoxicity - Aquatic Toxicity

# Material Safety Data Sheet

Material Name: Tin Scrap

ID: NFE-0106

## Arsenic (7440-38-2)

LC50 (96 hr) rainbow trout: 13.34 mg/L. Cond: Static.; LC50 (96 hr) fathead minnow: 15.66 mg/L.  
Cond: Flow-through.; LC50 (96 hr) bluegill (juvenile): 41.76 mg/L. Cond: Flow-through; EC50 (48 hr)  
water flea: 3.80-5.28 mg/L. Cond: Static.

## Environmental Fate

No information available for the product.

### \*\*\* Section 13 - Disposal Considerations \*\*\*

## US EPA Waste Number & Descriptions

### A: General Product Information

This product contains a component or components identified as hazardous under 40 CFR 261.24.

### B: Component Waste Numbers

#### Lead (7439-92-1)

RCRA: waste number D008; regulatory level = 5.0 mg/L

#### Silver (7440-22-4)

RCRA: waste number D011; regulatory level = 5.0 mg/L

#### Cadmium (7440-43-9)

RCRA: waste number D006; regulatory level = 1.0 mg/L

#### Arsenic (7440-38-2)

RCRA: waste number D004; regulatory level = 5.0 mg/L

## Disposal Instructions

Byproducts and residues from this product may be reprocessed or recycled. Upon disposal, collected dusts and other similar wastes could contain a constituent identified as a hazardous waste. Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes.

### \*\*\* Section 14 - Transportation Information \*\*\*

## US DOT Information

**Shipping Name:** Certain forms of this material (i.e. powders, borings, shavings, turnings, cuttings, dross, etc.) may be subject to U.S. DOT hazardous material shipping requirements. If products are shipped in quantities which exceed the reportable quantity (RQ) for individual components, they may also meet the requirements as DOT hazardous materials.

**Hazard Class:** Not available.

**UN/NA #:** Not available.

**Packing Group:** Not available.

**Required Label(s):** Not available.

**Additional Info.:** Not available.

### \*\*\* Section 15 - Regulatory Information \*\*\*

## US Federal Regulations

### A: General Product Information

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication). The following component analysis applies only to those facilities that are required to report under applicable regulations.

### B: Component Analysis

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

# Material Safety Data Sheet

**Material Name:** Tin Scrap

**ID:** NFE-0106

**Lead (7439-92-1)**

SARA 313: form R reporting required for 0.1% de minimus concentration  
 CERCLA: final RQ = 10 pounds (4.54 kg)

**Antimony (7440-36-0)**

SARA 313: form R reporting required for 1.0% de minimus concentration  
 CERCLA: final RQ = 5000 pounds (2270 kg) (no reporting of releases of this hazardous substance is required if the diameter of the pieces of solid metal released is equal to or exceeds 0.004 inches)

**Copper (7440-50-8)**

SARA 313: form R reporting required for 1.0% de minimus concentration  
 CERCLA: final RQ = 5000 pounds (2270 kg) (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is equal to or exceeds 0.004 inches)

**Silver (7440-22-4)**

SARA 313: form R reporting required for 1.0% de minimus concentration  
 CERCLA: final RQ = 1000 pounds (454 kg) (no reporting of releases of this hazardous substance is required if the diameter of the solid metal released is equal to or exceeds 0.004 inches)

**Cadmium (7440-43-9)**

SARA 313: form R reporting required for 0.1% de minimus concentration  
 CERCLA: final RQ = 10 pounds (4.54 kg) (No reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is equal to or exceeds 0.004 inches)

**Arsenic (7440-38-2)**

SARA 313: form R reporting required for 0.1% de minimus concentration  
 CERCLA: final RQ = 1 pound (0.454 kg) (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal release is equal to or exceeds 0.004 inches)

**C: Component Marine Pollutants**

This material contains one or more of the following chemicals required by US DOT to be identified as marine pollutants.

Component	CAS #	
Copper	7440-50-8	(as Copper metal powder); DOT regulated severe marine pollutant

**State Regulations**

**A: General Product Information**

Other state regulations may apply. Check individual state requirements.

**B: Component Analysis - State**

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS #	CA	FL	MA	MN	NJ	PA
Tin	7440-31-5	Yes	Yes	Yes	Yes	Yes	Yes
Lead	7439-92-1	Yes	Yes	Yes	Yes	Yes	Yes
Antimony	7440-36-0	Yes	Yes	Yes	Yes	Yes	Yes
Copper	7440-50-8	Yes	Yes	Yes	Yes	Yes	Yes
Silver	7440-22-4	Yes	Yes	Yes	Yes	Yes	Yes
Cadmium	7440-43-9	Yes	Yes	Yes	Yes	Yes	Yes
Arsenic	7440-38-2	Yes	Yes	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer.

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects.

**Other Regulations**

**A: General Product Information**

No information available for the product.

# Material Safety Data Sheet

Material Name: Tin Scrap

ID: NFE-0106

## B: Component Analysis - Inventory

	CAS #	TSCA	DSL	EINECS
Tin	7440-31-5	Yes	Yes	Yes
Lead	7439-92-1	Yes	Yes	Yes
Antimony	7440-36-0	Yes	Yes	Yes
Copper	7440-50-8	Yes	Yes	Yes
Silver	7440-22-4	Yes	Yes	Yes
Cadmium	7440-43-9	Yes	Yes	Yes
Arsenic	7440-38-2	Yes	Yes	Yes

## C: Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Tin	7440-31-5	1% item 1571 (804)
Lead	7439-92-1	0.1% item 937 (1435)
Antimony	7440-36-0	1% item 122 (251)
Copper	7440-50-8	1% item 433 (578)
Silver	7440-22-4	1% item 1414 (256)
Cadmium	7440-43-9	0.1% item 287 (378)
Arsenic	7440-38-2	0.1% item 130 (266)

### \*\*\* Section 16 - Other Information \*\*\*

#### Other Information

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use.

#### Key/Legend

EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; TLV = Threshold Limit Value; NFPA = National Fire Protection Association; HMIS = High Efficiency Particulate Air; CERCLA = Comprehensive Environmental Response, Compensation and Liability Act; SARA = Superfund Amendments and Reauthorization Act.

This is the end of MSDS # NFE-0106